

## NARROWBOAT BILGE PAINT

Issue Date 09/09/09

### PRODUCT DESCRIPTION

Narrowboat Bilge Paint is a single-pack polyurethane, hard wearing coating designed for application to bilge areas.

Narrowboat Bilge Paint offers outstanding film hardness and toughness. Narrowboat Bilge Paint has good resistance to oils, and water, this makes it an ideal choice for use in marine environments.

### COLOUR RANGE

British Standard Colours: BS; 4800 and 381c. RAL Shades.

### PACKAGING

1 litre tins

### HOW TO USE

Brush or Roller

### TECHNICAL INFORMATION

Appearance Of Dried Film:	Low sheen, textured finish.
Volume Solids:	50% (may vary with colour).
Spreading Rate:	Typically 8m <sup>2</sup> per litre
Drying Time At 20oC:	
Touch Dry:	3 hours.
Firm Dry:	6 hours (Will vary with Temperature, air movement etc.).
Overcoat:	Overnight.
Shelf Life:	2 years or longer in unopened containers when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5oC to 32oC.
Clean-Up:	Narrowboat Thinner R1

### PREPERATION

Ensure existing coating is firm and sound with good adhesion, Thoroughly clean with detergent water, adhesion will be improved if cleaned using a green or red scotchbrite pad, rinse and dry-off.

### APPLICATION

Apply by brush or roller. Apply one full coat. Bilge Paint can be brushed or rolled. Ensure paint film is fully cured before using the bilge. Ventilate the area as much as possible during application.

Application temperatures, avoid applying in very warm weather, remember, panel temperatures may be higher than the air temperature. Air movement will also accelerate drying. Avoid application on very cold or wet days as the risk of blooming (white mist over panels) or loss of gloss may occur.

Further advice on application is available on the Quick Guide – Repainting your Narrowboat



Please remember to stir our products thoroughly prior to use. For best results shake the tin prior to opening or place upside down to allow any settled pigments do disperse in the tin. Ideally, use a flat edge pallet knife with a minimum of 3/4 inch blade (or similar). Ensure that residues from the bottom of the tin are dispersed throughout. Colour match and product performance will be affected if this product is not thoroughly mixed.

**Great British  
Paint**



## HEALTH AND SAFETY

Refer to health and safety data sheet prior to use.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. Such information is to the best of Rapidpaint's knowledge and belief accurate and reliable as of the date indicated. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. For Professional Use Only. Ref:25

**Technical Data Sheets are also available on our website at**  
**[www.narrowboatcolours.co.uk](http://www.narrowboatcolours.co.uk)**



197-199 Bradford Street, Birmingham B12 0JD

Tel: 0121 693 4020  
Fax: 0121 693 5665  
Mail: [sales@rapidpaint.co.uk](mailto:sales@rapidpaint.co.uk)



*Narrowboat Paint Brand is manufactured solely by Rapidpaint*

**Great British  
Paint**

