

## NARROWBOAT BITUMEN

Issue date 09/09/09

### PRODUCT DESCRIPTION

Bitumen solution. Typical used for the protection of steel hulls, Outstanding water resistance.

### COLOUR RANGE

Colour - Black (Sheen finish)

### PACKAGING

5 litre containers

### HOT TO USE

Brush, Roller or Conventional Spray

### TECHNICAL INFORMATION

Volume Solids:	50%
Dry Film Thickness:	Typical: 50 Microns.
Theoretical Coverage:	10m <sup>2</sup> per litre at 50 microns dry film thickness.
Drying Time At 20oC:	Touch Dry: 4 Hours (Will Vary With Temperature, Air Movement etc.).
Overcoat:	After 16 Hours
Shelf Life:	2 years or longer in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5oC to 32oC.
Clean-Up:	Narrowboat Thinner R1 or R70.

### PREPARTION

Steel, thoroughly wire brush to remove all rust, mill-scale, etc. Degrease with Narrowboat Paint Thinner R70 or R1. A coat of Anti-Corrosive Primer (e.g. Narrowboat Red Oxide Primer, or Spraybuild Primer) is advisable on shotblasted hulls to prolong the life of the coating.

### APPLICATION

Two coats recommended.

Up to 5% of Narrowboat Thinner R70 may be added to achieve optimum spray characteristics.

### HEALTH AND SAFETY

Refer to health and safety data sheet prior to use.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. Such information is to the best of Rapidpaint's knowledge and belief accurate and reliable as of the date indicated. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. For Professional Use Only. Ref:25

**Technical Data Sheets are also available on our website at**

**[www.narrowboatcolours.co.uk](http://www.narrowboatcolours.co.uk)**

**RAPID***paint*  
THE PAINT FACTORY

197-199 Bradford Street, Birmingham B12 0JD

Tel: 0121 693 4020  
Fax: 0121 693 5665  
Mail: [sales@rapidpaint.co.uk](mailto:sales@rapidpaint.co.uk)



*Narrowboat Paint Brand is manufactured solely by Rapidpaint*

