

NARROWBOAT DETAILING PAINT

Issue date 09/09/09

PRODUCT DESCRIPTION

Narrowboat Detailing Paint has been formulated for decorative work to the boat and is ideally suited for boat names, roses & castles and other canal artwork. Narrowboat Detailing Paint dries to a matt finish and must be overcoated with varnish, we recommend Narrowboat Varnish. It is available in a range of popular colours complimentary to the topcoat.

COLOUR RANGE

Narrowboat Colour Chart.

PACKAGING

Available in 500ml containers.

HOW TO USE

Brush

TECHNICAL INFORMATION

Solids	Approximately 65-70% dependent on colour
Flashpoint	Above 32°C
Specific Gravity	1.30 to 1.50 approximately dependent on colour
Viscosity	2.5 - 3.5 ICI Cone And Plate
Storage	12 months in original sealed containers
Touch dry	3 hours
Firm dry	16 hours
Hard dry	7 days
Thinners	11 or White Spirit
Overcoating	6 hours minimum, maximum indefinite
Eqp. cleaning	White Spirit
Film thickness	70 microns WFT gives approximately 30 microns DFT
Coverage	10 square metres per litre (theoretical)
VOC	390g/l approximately

See application data

PREPARATION

De-nibb panel to be painted with a fine grade wet & dry or scotchbrite.

APPLICATION

Apply with brush. One coat is normally sufficient. Application of a second coat may be necessary on strong colours. Overcoat with Narrowboat Varnish when you are satisfied with the finish.

Application temperatures, avoid applying in very warm weather, remember, panel temperatures may be higher than the air temperature. Air movement will also accelerate drying. Avoid application on very cold or wet days.

Further advice on application is available on the Quick Guide – Repainting your Narrowboat



Please remember to stir our products thoroughly prior to use. For best results shake the tin prior to opening or place upside down to allow any settled pigments to disperse in the tin. Ideally, use a flat edge pallet knife with a minimum of 3/4 inch blade (or similar). Ensure that residues from the bottom of the tin are dispersed throughout. Colour match and product performance will be affected if this product is not thoroughly mixed.

**Great British
Paint**



NARROWBOAT DETAILING PAINT

Issue date 09/09/09

HEALTH AND SAFETY

Refer to health and safety data sheet prior to use.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. Such information is to the best of Rapidpaint's knowledge and belief accurate and reliable as of the date indicated. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. For Professional Use Only. Ref:25

Technical Data Sheets are also available on our website at
www.narrowboatcolours.co.uk



197-199 Bradford Street, Birmingham B12 0JD

Narrowboat Paint Brand is manufactured solely by Rapidpaint

Tel: 0121 693 4020
Fax: 0121 693 5665
Mail: sales@rapidpaint.co.uk

