

NARROWBOAT VARNISH

Issue date 09/09/09

PRODUCT DESCRIPTION

Narrowboat Varnish is a super durable single pack marine varnish based on innovative polymer materials. Narrowboat Varnish offers outstanding physical properties including exceptional film build, ultra high gloss and excellent ultraviolet resistance. Narrowboat Varnish is also used as a finishing coat over Narrowboat Detailing Paint. Can also be applied over Narrowboat Topcoats to create a varnished look to your boat. Its ease of usage and high performance make it the first choice marine varnish for many boat owners. Superb U-V resistance, High build and Ultra high gloss.

PACKAGING

Available in 1litre tins.

HOW TO USE

Brush or Roller

TECHNICAL INFORMATION

Solids	Approximately 55% by weight
Flashpoint	Above 32°C
Specific Gravity	1.10 to 1.30 approximately
Storage	12 months in original sealed containers
Colour retention	Excellent
Touch dry	5 hours
Hard dry	16 - 24 hours
Thinners	THINNER 11
Overcoating	24hrs minimum
Eqp. Cleaning	White Sprit
Environment	Marine
Film thickness	100 microns WFT gives approximately 40 microns DFT
Coverage	10 square metres per litre
VOC	440g/l
See application data	

PREPARATION

Surfaces must be clean, free from dust & totally dry. Knotting solution may be used if appropriate.

APPLICATION

Narrowboat Varnish is usually applied by brush straight from the tin. However, up to 10% of thinner 11 may be added to aid application if required. Normal application would be 2 to 3 coats of the Narrowboat Varnish to give the desired gloss/build.

Application temperatures, avoid applying in very warm weather, remember, panel temperatures may be higher than the air temperature. Air movement will also accelerate drying. Avoid application on very cold or wet days as the risk of blooming (white mist over panels) or loss of gloss may occur.

Further advice on application is available on the Quick Guide – Repainting your Narrowboat



**Great British
Paint**



HEALTH AND SAFETY

Refer to health and safety data sheet prior to use.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. Such information is to the best of Rapidpaint's knowledge and belief accurate and reliable as of the date indicated. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO IT'S ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. For Professional Use Only. Ref:25

Technical Data Sheets are also available on our website at
www.narrowboatcolours.co.uk



197-199 Bradford Street, Birmingham B12 0JD

Tel: 0121 693 4020
Fax: 0121 693 5665
Mail: sales@rapidpaint.co.uk



Narrowboat Paint Brand is manufactured solely by Rapidpaint

**Great British
Paint**

